

BSG30 | BSG50



STACKED

Washer-Extractor / Tumble dryer

FEATURES

- Ideal for limited space settings
- Increases wash capacity
- Improves throughput
- Minimal front fasteners give quick access to key washer-extractor components to improve serviceability
- Supports a higher volume than typical retail and light commercial products are able to support
- More than double production with higher capacity and faster wash times
- Reliability and durability that drastically outperforms retail or light commercial options
- IPSO stacked washer-extractor/tumble dryer is a unique product that truly delivers increased productivity.
- Featuring the Evolis Touch Control.

CONTROLS OPTIONS

- Available with EVOLIS touch control for Vend.
- 7", full color touch screen display with swipe function: very intuitive for users
- User-friendly screen with operating instructions built in as part of the control
- Complete control content available in 34 languages
- Wireless communication enabling programming & firmware updates through cloud
- Automated service reminders remind users to maintenance tasks
- Warranty IPSO Connect: interactive dashboard offers operational performance info on mobile device
- 5 standard dry programmes (High, Medium, Low, Delicate, No Heat)
- 15 easy-to-use washer cycle modifier



FIRE SUPPRESSION SYSTEM

For maximal safety of your operations



LOW ENERGY CONSUMPTION

Lower energy and utility costs, lower linen replacement costs



CLOUD-BASED PLATFORM

To easily monitor your laundry everywhere and at any time



EXTRA LARGE DOOR OPENING

For easy loading and unloading



HIGH CAPACITY WATER INLETS

For shorter wash cycles

YOUR SMART LAUNDRY PARTNER

Distributor by:
Retology No.1
AUTHORIZED DISTRIBUTOR

+628111 687746 +628111 867746
sales@ipsoindonesia.com
www.ipsoindonesia.com

		BSG30		BSG50	
		Washer-Extractor	Tumble Dryer	Washer-Extractor	Tumble Dryer
Control Option	kg (lb)	EVOLIS Touch		EVOLIS Touch	
Capacity Overall	mm (in)	30 (13.6) x 2		50 (23) x 2	
Width	mm (in)	31.4 (797)		34.4 (875)	
Overall Depth	mm (in)	45.5 (1152)		51.3 (1302)	
Overall Height	mm (in)	79.7 (2023)		84.3 (2141)	
Cylinder Diameter	mm (in)	24.0 (610)	30.0 (762)	26.3 (668)	33.0 (838)
Cylinder Depth	mm (in)	16.0 (406)	26.0 (660)	20.3 (515)	30.0 (762)
Cylinder Volume	cu. ft (liters)	4.2 (119)	10.6 (300)	6.3 (178)	14.8 (419)
Reversing Cylinder	mm (in)	-	Standard	-	Standard
Door Opening Size	mm (in)	14.3 (363)	22.6 (574)	16.3 (414)	26.9 (683)
Door Bottom to Floor	mm (in)	14.0 (356)	51.3 (1303)	14.6 (370)	52.3 (1328)
Water Inlet	mm (in)	2 x 0.75 (19)	-	2 x 0.75 (19)	-
Connection Drain	mm (in)	1 x 3 (76)	-	1 x 3 (76)	-
Diameter	mm (in)	4.3 (108)	-	4.5 (115)	-
Drain Height to Floor	Btu/hr (kW, Mj/hr.)	-	73,000 (21.4, 77.0)	-	95,000 (27.8, 100)
Heat Input Power	in	-	1/2 NPT	-	1/2 NPT
Gas Connection	mm (in)	-	8.0 (200) Elliptical	-	10.0 (250) Elliptical
Air Outlet	cfm (l/sec)	-	400 (190)	-	600 (285)
Airflow	kw	Fan	0.5 (0.4)	-	0.5 (0.4)
Motor	Drive	1 (0.75)	0.3 (0.2)	2 (1.5)	0.3 (0.2)
		9	-	9	-
Total # of Speeds	Gentle	34 (0.4)	-	33 (0.4)	-
Cylinder Speeds	Wash	48 (0.8)	-	46 (0.8)	-
- RPM (G-Force)	Distribution	86 (2.5)	-	82 (2.5)	-
	Very Low	282 (27)	-	269 (27)	-
	Low	485 (80)	-	464 (80)	-
	Medium	542 (100)	-	518 (100)	-
	High	606 (125)	-	579 (125)	-
	Very High	664 (150)	-	635 (150)	-
	Ultra High	766 (200)	-	733 (200)	-
Electrical	Gas				
Specs - amps	x	200-240V/50/60/1/3	15	10	15
Shipping	Width		34.5 (876)		35.5 (902)
Dimensions	mm (in)	Depth	47.0 (1194)		54.0 (1372)
Approx.	Height		83.0 (2108)		89.0 (2261)
Net Weight	lb(kg)		770 (349)		910 (413)
Shipping Weight	lb(kg)		787 (357)		930 (422)
Agency Approvals			CSA/UL/KGS/KTL/TISI/Global-Mark		CSA/UL/KGS/KTL/TISI/Global-Mark